

FORM PTO-1390  
(REV. 11-2000)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER  
P/61834-PCT

**TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)

10/088827

INTERNATIONAL APPLICATION NO.  
PCT/GB00/03644

INTERNATIONAL FILING DATE  
September 22, 2000

PRIORITY DATE CLAIMED  
September 23, 1999

TITLE OF INVENTION **A DROPLET GENERATOR FOR A CONTINUOUS STREAM INK JET PRINT HEAD**

APPLICANT(S) FOR DO/EO/US **Sukbir Singh PANNU**

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371 (f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☐ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
  - a. ☒ is attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ has been communicated by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
  - a. ☐ is attached hereto.
  - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
  - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ have been communicated by the International Bureau.
  - c. ☒ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

**Items 11 to 20 below concern document(s) or information included:**

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
14. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☒ Other items or information: **Receipt Acknowledgement Postcard**

U.S. APPLICATION NO (if known, see 37 CFR 1.5) <b>10/088827</b>		INTERNATIONAL APPLICATION NO <b>PCT/GB00/03644</b>		ATTORNEY'S DOCKET NUMBER <b>P/61834-PCT</b>	
--	--	---	--	--	--

21. <input checked="" type="checkbox"/> The following fees are submitted: <b>BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :</b> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... \$1,040.00  International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... \$890.00  International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... \$740.00  International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... \$710.00  International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) ..... \$100.00  <b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>				<b>CALCULATIONS PTO USE ONLY</b>          	
				\$890.00	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).				\$0.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$	
Total claims	9 - 20 =	0	x \$18.00	\$0.00	
Independent claims	2 - 3 =	0	x \$84.00	\$0.00	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$280.00	\$0.00	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				\$890.00	
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				\$0.00	
<b>SUBTOTAL =</b>				\$890.00	
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$0.00	
<b>TOTAL NATIONAL FEE =</b>				\$890.00	
Fee for recording the enclosed assignment (37 CFR 1.21 (h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). <b>\$40.00</b> per property +				\$0.00	
<b>TOTAL FEES ENCLOSED =</b>				\$890.00	
				Amount to be refunded:	\$
				charged:	\$

a. ☒ A check in the amount of **\$890.00** to cover the above fees is enclosed.

b. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 11-1145.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.**

**SEND ALL CORRESPONDENCE TO:**

**KIRSCHSTEIN, OTTINGER, ISRAEL & SCHIFFMILLER, P.C.**  
 489 Fifth Avenue  
 New York, New York 10017  
 (212) 697-3750

SIGNATURE:

**Alan Israel**  
 NAME  
**27,564**  
 REGISTRATION NUMBER

*I hereby certify that this correspondence is being deposited with the U.S. Postal Service as Express Mail No. EL 337 912 091 US in an envelope addressed to: Box: PCT, Commissioner of Patents and Trademarks, Washington, D.C., 20234, on: March 22, 2002*

(date)

*Alan Israel*

*Reg. No. 27,564*



**IN THE CLAIMS:**

Please cancel claims 1-9, without prejudice.

Please add the new set of claims 10-18 set forth on the enclosed pages.

**IN THE ABSTRACT:**

Delete the "Abstract" on the PCT cover sheet and replace it with the "Abstract of the Disclosure" set forth on a separate sheet attached hereto.

**REMARKS**

An abstract has been provided on a separate sheet; and the claims have been amended to conform to U.S. practice.

Wherefore, an early action on the merits is earnestly solicited.

Respectfully submitted,

KIRSCHSTEIN, OTTINGER, ISRAEL & SCHIFFMILLER, P.C.  
Attorneys for Applicant(s)  
489 Fifth Avenue  
New York, New York 10017-6105  
Tel: (212) 697-3750  
Fax: (212) 949-1690



---

Alan Israel  
Registration No. 27,564

### **ABSTRACT OF THE DISCLOSURE**

A droplet generator for a continuous stream ink jet print head includes an elongate cavity for containing the ink and nozzle orifices in a wall of the cavity for passing ink from the cavity to form jets. The nozzle orifices extend along the length of the cavity. An actuator is disposed on the opposite side of the cavity to the wall for vibrating the ink in the cavity such that each jet breaks up into ink droplets. In operation of the generator, a standing wave is present in the ink in the cavity. The cross-sectional area of the cavity varies along its length in a manner so as to tailor the form of the standing wave in the cavity such that each jet breaks up into the ink droplets at a respective predetermined distance from the wall of the cavity.

**PROPOSED NEW CLAIMS**

10. A droplet generator for a continuous stream ink jet print head, comprising:

- a) an elongate cavity for containing ink;
- b) nozzle orifices in a wall of the cavity for passing the ink from the cavity to form jets, said nozzle orifices extending along a length of the cavity;
- c) actuator means disposed on an opposite side of the cavity to said wall for vibrating the ink in the cavity such that each said jet breaks up into ink droplets, a standing wave being present in the ink in the cavity during operation of the generator; and
- d) said cavity having a cross-sectional area which varies along said length in a manner so as to tailor a form of said standing wave in the cavity such that each said jet breaks up into the ink droplets at a respective predetermined distance from said wall of the cavity.

11. The generator according to claim 10, wherein the form of said standing wave is tailored such that each said jet breaks up into the ink droplets at substantially the same predetermined distance from said wall of the cavity.

12. The generator according to claim 11, wherein the cross-sectional area of the cavity varies cyclically along said length between minimum and maximum values, said cross-sectional area having the minimum value whereat said standing wave has a region of low acoustic pressure at the nozzle orifices, said cross-sectional area having the maximum

value whereat said standing wave has a region of high acoustic pressure at the nozzle orifices.

13. The generator according to claim 12, wherein said cross-sectional area varies sinusoidally along said length.

14. The generator according to claim 11, wherein said cavity has a generally triangular cross-section.

15. The generator according to claim 11, wherein said cavity has a generally rectangular cross-section.

16. A method of operating a droplet generator for a continuous stream ink jet print head, comprising the steps of:

- a) containing ink in an elongate cavity having a length and a cross-sectional area;
- b) passing the ink from the cavity through nozzle orifices in a wall of the cavity to form jets, the orifices extending along the length of the cavity;
- c) vibrating the ink in the cavity such that each said jet breaks up into ink droplets, a standing wave being present in the ink in the cavity during operation of the generator;
- d) varying the cross-sectional area of the cavity along said length to tailor a form of the standing wave in the cavity such that each said jet breaks up into the ink droplets at a respective predetermined distance from said wall of the cavity; and

e) permitting parameters of the operation of the generator to stray such that the cavity operates over a range extending substantially all the way between two successive resonances along the length of the cavity.

17. The method according to claim 16, wherein said parameters of the operation permitted to stray are ink composition and temperature.

18. The method according to claim 16, wherein said cavity operates at substantially midway between the two successive resonances along the length of the cavity.



A Droplet Generator for a Continuous Stream Ink Jet Print Head

This invention relates to a droplet generator for a continuous stream ink jet print head.

More particularly the invention relates to such a generator comprising: an elongate  
5 cavity for containing the ink; nozzle orifices in a wall of said cavity for passing ink from the  
cavity to form jets, said nozzle orifices extending along the length of said cavity; and actuator  
means disposed on the opposite side of said cavity to said wall for vibrating the ink in said  
cavity such that each said jet breaks up into ink droplets, in operation of said generator a  
standing wave being present in the ink in said cavity.

10 An example of a generator as described in the preceding paragraph is disclosed in US-  
A-5,502,473. The generator of US-A-5,502,473 is designed to operate at, or very close to, a  
frequency at which its ink cavity is resonant in the vertical direction, i.e. from the actuator  
means to the nozzle orifices. This requires a very high accuracy in the physical dimensions of  
the structural components of the generator. It also permits very little stray in operating  
15 parameters of the generator such as ink composition and temperature.

US-A-4,827,287 discloses a droplet generator for a continuous stream ink jet print  
head. In this generator, in order to achieve the required jet break up, a travelling wave is  
caused to travel along an elongate nozzle orifice containing plate by means of the direct  
physical vibration of one end of the plate. The area of the plate free to vibrate is narrowed in  
20 the direction of wave propagation to compensate for attenuative losses. US-A-4,827,287 uses  
what is called a waveguided construction.

According to the present invention there is provided a droplet generator for a  
continuous stream ink jet print head comprising: an elongate cavity for containing the ink;  
nozzle orifices in a wall of said cavity for passing ink from the cavity to form jets, said nozzle

orifices extending along the length of said cavity; and actuator means disposed on the opposite side of said cavity to said wall for vibrating the ink in said cavity such that each said jet breaks up into ink droplets, in operation of said generator a standing wave being present in the ink in said cavity, characterised in that the cross-sectional area of said cavity varies along its length  
5 in a manner so as to tailor the form of said standing wave in the cavity such that each said jet breaks up into ink droplets at a respective predetermined distance from said wall of the cavity.

Preferably, the tailoring of the form of said standing wave is such that each said jet breaks up into ink droplets at substantially the same predetermined distance from said wall of the cavity.

10 Preferably, in the case of the preceding paragraph, the cross-sectional area of the cavity varies cyclically along its length between minimum and maximum values, said cross-sectional area having a minimum value whereat said standing wave has a region of low acoustic pressure at the nozzle orifices, said cross-sectional area having a maximum value whereat said standing wave has a region of high acoustic pressure at the nozzle orifices. The cyclical  
15 variation is for example sinusoidal.

In the case of each of the preceding two paragraphs, the cavity suitably has a generally triangular or a generally rectangular cross-section.

The invention also provides a method of operating a generator according to each of the preceding three paragraphs wherein the parameters of the operation of the generator are  
20 permitted to stray such that said cavity operates over a range extending substantially all the way between two successive resonances in the length of the cavity. Typically the parameters of the operation permitted to stray are ink composition and temperature.

The invention further provides a method of operating a generator according to each of the aforementioned three paragraphs wherein the cavity operates at substantially midway

between two successive resonances in the length of the cavity.

A droplet generator in accordance with the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is an end view of the generator;

5 Figure 2 is a side view of the generator;

Figures 3a) and 3b) are plan and perspective views respectively of an elongate ink cavity of the generator;

Figures 4a) and 4b) illustrate respectively the ink cavity's minimum and maximum cross-sectional area;

10 Figure 5 is a perspective view of a known elongate ink cavity;

Figure 6 is a cross-section of the known ink cavity;

Figure 7 illustrates, at each of a series of operating frequencies, contours of peak acoustic pressure within a plane extending along the known ink cavity;

Figure 8 compares ink cavity peak acoustic pressure when using the known ink cavity  
15 of Figures 5 and 6 to that when using the ink cavity of Figures 3 and 4; and

Figure 9 is a perspective view of an alternative ink cavity according to the present invention.

Referring to Figures 1 and 2, the generator comprises a polyetheretherketone manifold 1, and, push fitted therein, an actuator 3 and a nozzle carrier 5. Actuator 3 comprises a  
20 piezoelectric driver 9, a stainless steel head 11 and a brass backing member 6. Nozzle carrier 5 comprises a stainless steel element 2 defining therein a 'V' cross section channel, and, bonded to element 2, a stainless steel foil sheet 10. Sheet 10 contains a line of nozzle orifices 7, and is so bonded to element 2 that this line runs along the length of the open apex of the 'V' cross section channel of element 2.

An elongate ink cavity 13 is defined by the lower face 15 of actuator 3 and interior faces 17, 19 of element 2 which define the 'V' cross section channel of element 2. Actuator 3 runs the length of cavity 13 and overlaps the ends and sides of cavity 13 at 31 and 33 respectively. A narrow gap 20 is present on either side of head 11 of actuator 3 between it and manifold 1. 'O' rings 21 seal against the further egression of ink from cavity 13 and gaps 20. Thus, piezoelectric driver 9 is sealed from contact with the ink. Channels (not shown) are provided in manifold 1 and communicate with gaps 20 for the supply of ink to cavity 13 and the bleeding of air/ink from cavity 13.

At the frequency of operation of the generator, actuator 3 has a vertical thickness resonance at which all points across the lower face 15 of actuator 3 vibrate vertically in phase and with the same amplitude, i.e. at which lower face 15 is driven in contact with the ink in cavity 13 in piston-like manner.

Cavity 13 is shaped so as to provide a steady and essentially unidirectional flow of ink to nozzle orifices 7. The reducing surface area in the direction of wave travel (i.e. from lower face 15 of actuator 3 to nozzle orifices 7) causes an increased acoustic pressure at the apex of the 'V' cross-section channel as compared to that at lower face 15.

Referring now also to Figures 3 and 4, interior faces 17, 19 of element 2 undulate sinusoidally in synchronism thereby to produce a 'V' cross-section body of ink 49 in cavity 13 having correspondingly undulating sides 51, 53, as shown in Figures 3 and 4. The undulation is greatest at the tops 55 of the sides 51, 53 and gradually reduces in the direction of the apex 57 of the 'V' to peter to zero thereat. The effect of the undulation is that the cross-sectional area of the elongate body of ink 49 varies cyclically along its length between minimum (Figure 4a) and maximum (Figure 4b)) values. The varying cross-sectional area of ink cavity 13 will be discussed further below.

At the frequency of operation of the generator of Figures 1 and 2, cavity 13 is non-resonant in the vertical direction, i.e. from lower face 15 of actuator 3 to line of nozzle orifices 7. This facilitates a relaxation in the required accuracy of the physical dimensions of the structural components of the generator. It also permits greater stray in operating parameters of the generator such as ink composition and temperature.

It is to be appreciated that if cavity 13 were to be designed to be resonant in the vertical direction, then it would be necessary at operating frequency for an integer number of half wavelengths to fit precisely in this vertical direction between lower face 15 of actuator 3 and line of nozzle orifices 7. A pure standing wave, extending in the vertical direction, would then be established. Thus, the acoustic pressure along line of nozzle orifices 7 would be the same, with the desirable result that the jets emanating from the orifices would break up into ink droplets at the same predetermined distance from the orifices. Such an arrangement, although advantageous in that uniform jet break up is conveniently achieved, is disadvantageous in that it is highly sensitive to inaccuracy in the structural dimensions and operating parameters of the generator.

Cavity 13 is also non-resonant along its length in operation of the generator. Thus, at operating frequency, an integer number of half wavelengths does not precisely fit into the length of cavity 13, and therefore a pure standing wave is not established which extends along cavity 13. Resonances along the length of cavity 13, so called resonance length modes, obviously occur at a series of frequencies. Thus, it is necessary that the generator be operated at a frequency that is between two successive length modes. It is to be understood that it would not be desirable to operate at a length mode frequency, since the acoustic pressure along line of nozzle orifices 7 would vary greatly. This variation would correspond to the nodes and antinodes of the established pure standing wave, and result in non-uniform jet break up.

Clearly, operation is ideally midway between two successive length modes.

As aforesaid, cavity 13 is operated at a frequency between two length modes. A standing wave is established in cavity 13, but not a pure standing wave as mentioned previously. The standing wave established is a partial standing wave, and is the resultant wave  
5 generated by multiple reflections at the walls of cavity 13. There will be further below discussion of the operation of the ink cavity of Figures 3 and 4.

Turning now to the known ink cavity of Figures 5 and 6, this ink cavity is the same as that shown in Figures 3 and 4 with the exception that its walls 61, 63 do not undulate but are  
flat and planar in form. Thus, the cross-sectional area of the known ink cavity does not vary  
10 but remains the same along its length. Figures 4a), 4b) and 6 are drawn to the same scale, thereby enabling comparison between the minimum and maximum cross-sectional areas of the body of ink 49 in cavity 13 and the cross-sectional area of the body of ink 65 in the known ink cavity.

Acoustic pressure variation within the known ink cavity will now be considered at each  
15 of a number of operating frequencies. In Figure 7 each plot is of contours of peak acoustic pressure, at a given operating frequency, within plane A drawn in Figure 6, which plane  
extends into the paper in Figure 6. Considering the 88 kHz plot, the 'peaks' 71 along the line of nozzle orifices represent regions of high acoustic pressure, and the 'troughs' 73 between  
peaks 71 represent regions of low acoustic pressure. It can be seen that the acoustic pressure  
20 along the nozzle orifices varies greatly, resulting in non-uniform jet break up. This is also so in the case of the plots at all other seven frequencies. Thus, satisfactory operation, i.e. uniform jet break up, is not achieved with the known ink cavity at the operating frequencies of Figure  
7.

A length mode resonance occurs at 91 kHz. Thus, at 91 kHz a pure standing wave is

established in the ink cavity. At the other seven frequencies a partial standing wave is established. An important feature to note is that both above and below 91 kHz, the regions of high and low acoustic pressure occur at the same spatial positions along the line of nozzle orifices. Thus, at 88 and 90 kHz the highs and lows occur at the same spatial positions. Similarly, at 92, 94, 96, 98 and 100 kHz the highs and lows occur at the same positions. Provided a length mode resonance frequency is not crossed, the spatial position of the highs and lows remains constant. In fact, in any given interval between two successive length modes, the spatial locations of the highs and lows are determined by the acoustic pattern of one of these two length modes, since it is this pattern that degenerates to provide the highs and lows between the two length modes. With reference to the 91 kHz plot and the higher frequency plots, the nine 'white stripe' highs of the 91 kHz plot degenerate in the higher frequency plots into five highs at the bottom of the ink cavity and four at the top.

Figures 8a) and 8c) are ink cavity peak acoustic pressure plots at generator operating frequency when using the known ink cavity of Figures 5 and 6 (Figure 8a)) and the ink cavity according to the present invention of Figures 3 and 4 (Figure 8c)). Figure 8b)) is a repeat of Figure 3a), and is drawn in line between Figures 8a) and 8c) to enable the relative positions of the acoustic pressure peaks and troughs of Figure 8a) to be compared to the undulations of the walls of the body of ink in Figure 8b). It can be seen that interior faces 17, 19 of element 2 of the generator are arranged to undulate so that body of ink 49 has a minimum cross-sectional area 81 whereat there is a region of low acoustic pressure 73, and a maximum cross-sectional area 83 whereat there is a region of high acoustic pressure 71. The effect of this is that the regions of high pressure are expanded to reduce the pressure thereat, and the regions of low pressure are constricted to increase the pressure thereat. The result is an evening-out of the acoustic pressure along the line of nozzle orifices as shown in Figure 8c), resulting in

the desired uniform jet break up.

The alternative ink cavity according to the present invention shown in Figure 9 is the same as that shown in Figures 3 and 4 with the exception that the cavity has a rectangular cross-sectional area rather than triangular. The design principle is the same, i.e. the walls 91, 93 of the cavity undulate sinusoidally in synchronism so that the cavity has a minimum rectangular cross-sectional area whereat there is a region of low acoustic pressure at the nozzle orifices, and has a maximum rectangular cross-sectional area whereat there is a region of high acoustic pressure.

A further disadvantage with the acoustic pressure pattern shown in Figure 8a) is that it is not possible to select a single drive voltage for piezoelectric driver 9 at which all jets meet the condition that they are satellite droplet free. The reason for this is that a given drive voltage does not 'appear' to have the same value at all nozzle orifices, because of the variation in acoustic pressure along the nozzle orifices. Thus, it is possible to select a drive voltage to meet the satellite free condition for say all the nozzle orifices in regions of low acoustic pressure, but adjustment of this voltage to meet the satellite free condition for the nozzle orifices in regions of high acoustic pressure takes the voltage outside the range that meets the satellite free condition for the low acoustic pressure nozzle orifices. The evening-out of acoustic pressure at the nozzle orifices shown in Figure 8c) solves this problem.

The generator described by way of example is operated at a frequency between two successive length modes. As pointed out previously, between two such modes the regions of high and low acoustic pressure do not change their spatial locations. Thus, provided operation is kept between the two modes, satisfactory operation will be achieved. Indeed, operation is only limited by the room between the two length modes, which, with a typical ink and a 50mm long cavity, would be about 10 kHz. This affords a very stable generator that is highly tolerant



of both inaccuracy in the structural dimensions of the generator, and stray in its operating parameters.

In the generator described above by way of example, the drive signal applied to the piezoelectric driver is assumed sinusoidal, single frequency. This generates sinusoidal variations in the acoustic pressure distribution in the ink cavity, and necessitates that the compensating variation in the cross-sectional area of the cavity be sinusoidal in nature. The use of an alternative form of piezoelectric drive signal would therefore require a corresponding alternative form of shape profile for the cavity walls, the precise nature of this profile in any given case being determined so as to compensate for, i.e. even-out, variation in acoustic pressure along the line of nozzle orifices.

A further advantage of the present invention is that unwanted acoustic variations caused by other sources can also be compensated for or negated as long as they are of a constant form. For example, an actuator can be used not operating in a perfect vertical thickness resonance, i.e. having some amplitude and/or phase variation in the vibration. This can be accounted for in the cavity shaping. The foregoing allows the use of longer transducers that are difficult to make without some lateral variation in vibration amplitude and phase.

It is to be appreciated that the invention can be utilized in the context of a generator designed to operate with its cavity resonant in the vertical direction. If in such a generator the actuator is not operating in a perfect vertical thickness resonance as desired, the effect of this on the acoustic pressure distribution in the cavity can be compensated for by appropriate shaping of the cavity walls.

In the droplet generator described above by way of example, the invention is utilised in operation between two length modes. It is to be appreciated that even at a length mode frequency, appropriate variation in the cross-sectional area of the ink cavity along its length

can be used to significantly 'flatten-out' acoustic pressure variation along the cavity.

In the above description there is present in a uniform cross-section ink cavity a standing wave the form of which is not as desired. This form is then tailored to improve it by varying the cross-sectional area of the cavity. In the description the tailoring is such as to achieve  
5 uniform jet break up. It can be imagined that the tailoring need not necessarily be such as to achieve uniform jet break up, but need simply be such as to achieve a desired jet break up profile along the line of nozzle orifices.

CLAIMS:

1. A droplet generator for a continuous stream ink jet print head comprising: an elongate cavity (13) for containing the ink; nozzle orifices (7) in a wall (10) of said cavity (13) for passing ink from the cavity (13) to form jets, said nozzle orifices (7) extending along the length of said cavity (13); and actuator means (3) disposed on the opposite side of said cavity (13) to said wall (10) for vibrating the ink in said cavity (13) such that each said jet breaks up into ink droplets, in operation of said generator a standing wave being present in the ink in said cavity (13), characterised in that the cross-sectional area of said cavity (13) varies along its length in a manner so as to tailor the form of said standing wave in the cavity (13) such that each said jet breaks up into ink droplets at a respective predetermined distance from said wall (10) of the cavity (13).
2. A generator according to claim 1 wherein the tailoring of the form of said standing wave is such that each said jet breaks up into ink droplets at substantially the same predetermined distance from said wall (10) of the cavity (13).
3. A generator according to claim 2 wherein the cross-sectional area of the cavity (13) varies cyclically along its length between minimum (81) and maximum (83) values, said cross-sectional area having a minimum value (81) whereat said standing wave has a region of low acoustic pressure at the nozzle orifices (7), said cross-sectional area having a maximum value (83) whereat said standing wave has a region of high acoustic pressure at the nozzle orifices (7).
4. A generator according to claim 3 wherein said cross-sectional area varies sinusoidally along its length (Figs. 3, 4 and 9).
5. A generator according to claim 2 or claim 3 or claim 4 wherein said cavity (13) has a generally triangular cross-section (Figs. 3 and 4).

6. A generator according to claim 2 or claim 3 or claim 4 wherein said cavity (13) has a generally rectangular cross-section (Fig. 9).
7. A method of operating a generator according to any one of claims 2 to 6 wherein the parameters of the operation of the generator are permitted to stray such that said cavity (13)  
5 operates over a range extending substantially all the way between two successive resonances in the length of the cavity (13).
8. A method according to claim 7 wherein said parameters of the operation permitted to stray are ink composition and temperature.
9. A method of operating a generator according to any one of claims 2 to 6 wherein said  
10 cavity (13) operates at substantially midway between two successive resonances in the length of the cavity (13).

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
29 March 2001 (29.03.2001)

PCT

(10) International Publication Number  
**WO 01/21406 A1**

(51) International Patent Classification<sup>7</sup>: B41J 2/025, 2/03

(21) International Application Number: PCT/GB00/03644

(22) International Filing Date:  
22 September 2000 (22.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
9922421.4 23 September 1999 (23.09.1999) GB

(71) Applicant (for all designated States except US): MARCONI CORPORATION PLC. [GB/GB]; One Bruton Street, London W1X 8AQ (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): PANNU, Sukbir, Singh [GB/GB]; 69 Broadway, Grantchester, Cambridge CB3 9NQ (GB).

(74) Agent: MCGOWAN, Nigel, George; Marconi Intellectual Property, Waterhouse Lane, Chelmsford, Essex CM1 2QX (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.



(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A DROPLET GENERATOR FOR A CONTINUOUS STREAM INK JET PRINT HEAD



(57) Abstract: A droplet generator for a continuous stream ink jet print head comprising : an elongate cavity (13) for containing the ink; nozzle orifices (7) in a wall (10) of said cavity (13) for passing ink from the cavity (13) to form jets, said nozzle orifices (7) extending along the length of said cavity (13); and actuator means (3) disposed on the opposite side of said cavity (13) to said wall (10) for vibrating the ink in said cavity (13) such that each said jet breaks up into ink droplets, in operation of said generator a standing wave being present in the ink in said cavity (13), characterised in that the cross-sectional area of said cavity (13) varies along its length in a manner so as to tailor the form of said standing wave in the cavity (13) such that each said jet breaks up into ink droplets at a respective predetermined distance from said wall (10) of the cavity (13).

WO 01/21406 A1




FIG. 2




FIG. 1

FIG. 4

3 / 5





FIG. 6





FIG. 9



FIG. 7





Type a plus sign (+) inside this box → ☐Approved for use through 9/30/98  
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

0010/PTO Rev. 6/95 U.S. Department of Commerce Patent and Trademark Office  <b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION</b>  <input type="checkbox"/> Declaration OR Submitted with Initial Filing <input checked="" type="checkbox"/> Declaration Submitted after Initial Filing	Attorney Docket Number	P/61834
	First Named Inventor	PANNU, SUKBI SINGH
	COMPLETE IF KNOWN	
	Application Number	10/088,827
	Filing Date	MARCH 22, 2002
	Group Art Unit	
Examiner Name		

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A DROPLET GENERATOR FOR A CONTINUOUS STREAM INK JET PRINT HEAD

(Title of the Invention)

the specification of which

☐ is attached hereto  
OR
☒ was filed on (MM/DD/YYYY)

MARCH 22, 2002

as United States Application Number or PCT International

Application Number

10/088,827

and was amended on (MM/DD/YYYY)

(if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119 (a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365 (a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
9922421.4	GB	September 23 1999	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>
PCT/GB00/03644	INTERNATIONAL	Sept. 22, 2000			

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto:

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

Burden Hour Statement: This form is estimated to take .4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231.

DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Type a plus sign (+) inside this box → ☐

# DECLARATION

Page 2

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application Number	PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority sheet attached hereto.

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Firm Name  Customer Number or label   
☒ OR  
☒ List attorney(s) and/or agent(s) name and registration number below:

Name	Registration Number	Name	Registration Number
David B. Kirschstein, Esq.	17,244		
Alan Israel, Esq.	27,564		
Martin W. Schiffmiller, Esq.	30,421		

☐ Additional attorney(s) and/or agent(s) named on a supplemental sheet attached hereto.

Please direct all correspondence to: ☐ Customer Number or label  OR ☒ Fill in correspondence address below

Name KIRSCHSTEIN, OTTINGER, ISRAEL & SCHIFFMILLER, P.C.

Address 489 Fifth Avenue

Address

City New York

State New York

ZIP 10017-6105

Country United States

Telephone (212) 697-3750

Fax (212) 949-1690

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name	<u>Sukbir</u>	Middle Initial		Family Name	<u>PANNU</u>	Suffix e.g. Jr.	
------------	---------------	----------------	--	-------------	--------------	-----------------	--

Inventor's Signature

X Sukbir Pannu

Date

2 APRIL 2002

Residence: City	<u>Grantchester, Cambridge</u>	State		Country	<u>United Kingdom</u>	Citizenship	<u>British</u>
-----------------	--------------------------------	-------	--	---------	-----------------------	-------------	----------------

Post Office Address 69 Broadway, Grantchester, Cambridge, CB3 9NQ, (GB) UK

Post Office Address

City	<u>Grantchester, Cambridge</u>	State		Zip	<u>CB3 9NQ</u>	Country	<u>United Kingdom</u>	Applicant Authority	
------	--------------------------------	-------	--	-----	----------------	---------	-----------------------	---------------------	--

☐ Additional inventors are being named on supplemental sheet(s) attached hereto